



# SLK-R602 Series

# Industrial 4G/3G Router

# Specification

**Data Sheet** 2015-6-6



Seriallink<sup>®</sup>

## SLK-R602 Series Outdoor 4G Router Data Sheet



### Introduction:

SLK-R602 is an industrial-grade high-speed wireless router based on GPRS/CDMA/WCDMA/EVDO/LTE cellular mobile network to provide users with high-speed wireless Internet and wireless data transmission functions.

This product adopts industrial-grade dedicated communication 32-bit RISC processors, industrial-strength wireless mold piece, the LINUX embedded real-time operating system, support a SIM card interface, four LAN, a WAN port, and WIFI interface, at the same time provide LAN port equipment or WIFI Internet or data transmission function.

It also adopts wide temperature, wide voltage input and EMC test with electromagnetic compatibility.

Has been widely used in the Internet of things industry chain of M2M industry, such as self-service terminals, smart grid, smart transportation, smart home, financial, mobile POS terminals, supply chain automation, industrial automation, intelligent buildings, fire control, public security, environmental protection, meteorology, digital medical treatment, telemetry, military, space exploration, agriculture, forestry, water, coal, petrochemical and other fields

### Features:

- ✓ LTE Band Support
  - EU Model: 2100/1800/2600/900/800 MHz (B1/B3/B7/B8/B20)
  - US Model: 1900/AWS/850/700/700/1900 MHz (B2/B4/B5/B13/B17/B25)
- ✓ Built-in high speed 2-port Ethernet switch, 2x LAN port
- ✓ 1X WAN port
- ✓ Power input supported DC12-28VDC
- ✓ The power and the antenna with lightning protection
- ✓ Support VPN client (PPTP, L2TP, OPENVPN, IPSEC and GRE) (only for VPN version)
- ✓ Support hardware and software WDT

**Details:**
**Cellular Interface :**

Cellular Interface		
<b>Band Supported</b>	4G/3G/2G Version	<ul style="list-style-type: none"> <li>•Supported TDD-LTE B38/B39/B40/B41</li> <li>•Supported FDD-LTE B1/B3/B5/B8</li> <li>•Supported FDD-LTE B1/ B3/ B5/ B7/ B8/B12/ B20</li> <li>•Supported FDD-LTE B1/ B2/ B3/ B4/ B5/ B7/ B8/ B28</li> <li>•Supported TD-SCDMA B34/B39</li> <li>•Supported WCDMA/HSDPA/HSPA+ B1/B8</li> <li>•Supported CDMA 1X/EVDO BC0</li> <li>•Supported GSM/GPRS/EDGE 900/1800 MHz</li> </ul>
	EVDO 3G Version	Supported EVDO, CDMA2000 1X
	HSDPA 3G Version	Supported HSUPA/HSDPA/UMTS/EDGE/GPRS/GSM
<b>Theory of Bandwidth</b>	<ul style="list-style-type: none"> <li>• LTE CAT4- DL : 50Mbps, UL : 150Mbps</li> <li>• TD-HSDPA/HSUPA-DL : 2.2 Mbps, UL : 2.8 Mbps</li> <li>• HSPA+-DL : 5.76 Mbps, UL : 42 Mbps</li> <li>• WCDMA – DL/UL : 384Kbps</li> <li>• CDMA2000/EVDO DL : 1.8 Mbps, UL : 3.1 Mbps</li> </ul>	

**WIFI Performance :**

WIFI supported	
<b>Standards</b>	Supported IEEE 802.11 b/g/n
<b>Frequency</b>	2.4GHz (ISM band supported)
<b>WIFI Rate</b>	150Mbps
<b>Security</b>	64/128-bit WEP (Wired Equivalent Privacy)
	WPA & WPA-PSK & WPA2 -PSK (Wi-Fi Protected Access)

**Router characteristics**

<b>Firewall</b>	Network Address Translation (NAT)
	State full Packet Inspection (SPI)
<b>Media Access Control</b>	CSMA/CA with ACK
<b>VPN protocol</b>	Supported IPSec, PPTP, L2TP
<b>DHCP</b>	Build-in DHCP (Dynamic Host Configuration Protocol)
<b>Others protocol</b>	Supported PPP, PPOE, DDNS, ICMP, VRRP etc

**Hardware :**

Hardware	
<b>CPU</b>	32-bit high performance communication CPU, 32bit/400MHZ



Flash/RAM	8M/64M
OS	LINUX latest version

**Interface:**

<b>Interface</b>	
LAN	1 x 10/100M port
WAN	1x 10/100M WAN/LAN port
Reset	1x Reset
Antennas	1x 3G/4G Antenna(50Ω SMA interface )
	1x WiFi or GPS antenna (option)
LED	Power-SYS-LAN-WiFi-3G/4G LED
SIM slot	Supported 1.8/3.3V SIM card we support SIM card converter meet all size sim card

**Power interface :**

<b>Power</b>	
Default power	DC 12V/1A power adapter (US,EU etc stander option)
Input VDC	12~28V
Power Dissipation	Min: 260mA@12VDC
	MAX: 500mA@12VDC
	Average:320mA@12VDC

**Physical property:**

<b>Operating</b>	
Temperature	Storage Temperature: (-40° C to 75° C)
	Operating Temperature: (-40° C to 65° C)
Relative Humidity	95%
Size	L*S*H: 98m x61.3mm x 23mm
Weight	Net weight:136g
	Packing weight:453kg

**Others:**

<b>other</b>	
Warranty	2 years
MTBF	17520 hour
Package contains	Seriallink Router,1.5m long RJ45 Cable,12V/1A Power Adapter,Antennas User manual( Option choose PDF) ,Warranty card, CERTIFICATION

**Order information:**

Model	LAN	WAN	SIM slot	WIFI/GPS	4G
-------	-----	-----	----------	----------	----




Seriallink®

# SLK-R602 Series Outdoor 4G Router Data Sheet

SLK-R602-_LTE	1	1	1	1	1
SLK-R602-_HSDPA	1	1	1	1	1
SLK-R602-_EVDO	1	1	1	1	1

**Product size drawing**  
Unit: mm



Thank you for your support of SERIALLINK products.

If you have any questions, please email: [info@seriallink.net](mailto:info@seriallink.net) or [www.seriallink.net](http://www.seriallink.net)



**Seriallink**<sup>®</sup>

**SLK-R602 Series Outdoor 4G Router Data Sheet**

---

SERIALLINK CONFIDENTIAL